



J26L637 26" LCD HDTV Healthcare Monitor-Receiver



ENERGY STAR[®]
Qualified



Pillow Speaker
Compatible



ClonePro[™]
Programming



HDTV/QAM
Digital Tuner



Side A/V Jacks



Internal Power Supply
with Safety Plug

For more information, call 1.800.333.7221.

J26L637 LCD HDTV



Picture Technology

Tuner	ATSC/NTSC/QAM
Category	LCD
Display Type	TFT LCD
Screen Size	26"
Display Aspect Ratio	16 x 9
Display Resolution	1366 x 768
Brightness (cd/m2)	500
Contrast Ratio	600:1
Viewing Angle Horizontal/Vertical	170/170
Response Time	8 ms

Sound Technology

Broadcast Stereo Sound
SAP (secondary audio program) where available
Audio Power front speakers 8 watts / channel x 2
Headphone Adjustments

Commercial Features

NTSC/ATSC/QAM Tuner for a wide range of options using off-air, satellite/cable or internally generated program signals.

Channel-Guide with One-Button Access for an on-screen listing of all available channels and their identification labels.

8-Character Channel Labeling allows for on-screen display of both network affiliation and channel number.

User Remote with TV1/TV2/TV3 Capability allows simultaneous control of multiple monitors in the same room.

ENERGY STAR® Qualification saves energy costs.

Power Provisions for Third-Party Modules eliminate the need for wall-transformers, wiring snarls and "set-top" boxes.

Digital Serial Communications Interface (DSCI) allows third-party interactive systems to monitor and control television with optimal performance and efficiency.

Pendant Jack features special healthcare isolation for optional pillow speakers, nurse-call units and bedside remote controls to provide the utmost in patient convenience and safety. Conforms to UL 6500 Annex H.

Configuration Menus with Non-Volatile Memory for site-specific specifications and limitations on how televisions can be operated and retained, even when power is lost.

Selectable Weak Signal Muting mutes audio, blanks video and provides an on-screen message if signal is weak or lost.

Selectable Clock and Scheduler with automatic time set allows TV signal to automatically set time (where available); scheduled turn on/off events can be one-time or recurring.

Volume Limiter and Initial Volume establish maximum and consistent initial volume settings each time television is turned on.

Selectable Automatic Turn-Off permits television to turn off automatically after a period of inactivity.

IR and Wired Cloning Capabilities allow rapid duplication of configuration information between televisions for ease of installation and maintenance.

Side Access A/V Jacks offer convenient connection of external audio or video components.

Front Panel Lockout prevents tampering.

Commercial Cabinet with Mountable Stand provides integral mounting ability.

Software Upgrade Port to upgrade firmware in the field.

Specifications


Inputs Rear: RF Input (ATSC/NTSC) • Composite Video Input
• Audio Input for Composite/S-Vid
• Dsub15 VGA • Audio input for RGB
• Component Video Input (Y/CrCb/YPrPb)
• Audio Input for Component Video
• DVI – HDMI™ • VGA Audio
• Audio input for DVI – HDMI™ (Menu Select)
• DSCI Jack • I2C Connector • Software Upgrade

Inputs Side: Composite Video Input • S-Video Input
• Audio input for Composite

Outputs Rear: Video Output • Audio Outputs

Outputs Side: Headphone Jack

Rear



Side



Power: Internal power supply 3-prong grounded safety plug

Power Requirements: 120VAC (+/-)10%, 60Hz

Power Consumption: Stand-by: less than 1 watt (ENERGY STAR Qualified)

Cabinet: Construction: high-impact flame-retardant polystyrene
Finish: black
Dimensions: 18.5"H, 31.0"W, 4.0"D
Dimensions with stand: 20.7"H, 31.0"W, 9.1"D
VESA mounting compatible: 400 x 200 hole pattern

Weight: Product 46.3 lbs. / Shipping 53.1 lbs.

Certification: UL Healthcare Listing

Limited Warranty: 1 year parts and labor

This television receiver provides display of television closed-captioning in accordance with §15.119 of the FCC rules. This television does not support color attributes of television closed-captioning.

Optional Accessories

ClonePRO™ Remote (CBX203)

This unique accessory significantly reduces installation and programming time, allowing you to program one television and then transfer the same data to all similar sets in just seconds. The more RCA televisions you install, the more efficiency you gain.



Master Remote (R130K2)

The RCA Master Remote maintains control of all setup menus, including audio and video functions.



©2006 TTE Technology, Inc.
www.rca.com/rcacommercial • Phone: 1-800-333-7221

Commercial Sales and Distribution • MS INH605
101 West 103rd Street • Indianapolis, Indiana 46290-1024

Printed in U.S.A. 3/06-5M

TV pictures simulated. Specifications subject to change without notice. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. RCA and associated marks are trademarks of THOMSON S.A. used under license to TTE Corporation.



J26L637-H-0



J26L637 26" LCD HDTV Commercial Monitor-Receiver



ENERGY STAR®
Qualified



Side AV Jacks




ClonePro™
Programming



HDTV/QAM
Digital Tuner



Internal Power Supply
with Safety Plug



Digital Serial
Communications
Interface

For more information, call 1.800.333.7221.

J26L637 LCD HDTV



Picture Technology

Tuner	ATSC/NTSC/QAM
Category	LCD
Display Type	TFT LCD
Screen Size	26"
Display Aspect Ratio	16 x 9
Display Resolution	1366 x 768
Brightness (cd/m2)	500
Contrast Ratio	600:1
Viewing Angle Horizontal/Vertical	170/170
Response Time	8 ms

Sound Technology

Broadcast Stereo Sound
SAP (secondary audio program) where available
Audio Power front speakers 8 watts / channel x 2
Headphone Adjustments

Commercial Features

NTSC/ATSC/QAM Tuner for a wide range of options using off-air, satellite/cable or internally generated program signals.

Channel-Guide with One-Button Access for an on-screen listing of all available channels and their identification labels.

8-Character Channel Labeling allows for on-screen display of both network affiliation and channel number.

User Remote with TV1/TV2/TV3 Capability allows simultaneous control of multiple monitors in the same room.

ENERGY STAR® Qualification saves energy costs.

Power Provisions for Third-Party Modules eliminate the need for wall-transformers, wiring snarls and "set-top" boxes.

Digital Serial Communications Interface (DSCI) allows third-party interactive systems to monitor and control television with optimal performance and efficiency.

Configuration Menus with Non-Volatile Memory for site-specific specifications and limitations on how televisions can be operated and retained, even when power is lost.

Selectable Weak Signal Muting mutes audio, blanks video and provides an on-screen message if signal is weak or lost.

Selectable Clock and Scheduler with automatic time set allows TV signal to automatically set time (where available); scheduled turn on/off events can be one-time or recurring.

Volume Limiter and Initial Volume establish maximum and consistent initial volume settings each time television is turned on.

Selectable Automatic Turn-Off permits television to turn off automatically after a period of inactivity.

IR and Wired Cloning Capabilities allow rapid duplication of configuration information between televisions for ease of installation and maintenance.

Side Access A/V Jacks offer convenient connection of external audio or video components.

Front Panel Lockout prevents tampering.

Commercial Cabinet with Mountable Stand provides integral mounting ability.

Software Upgrade Port to upgrade firmware in the field.

Specifications

Inputs Rear: RF Input (ATSC/NTSC) • Composite Video Input • Audio Input for Composite/S-Vid • Dsub15 VGA • Audio input for RGB • Component Video Input (Y/CrCb/YPrPb) • Audio Input for Component Video • DVI – HDMI™ • VGA Audio • Audio input for DVI – HDMI™ (Menu Select) • DSCI Jack • I2C Connector • Software Upgrade

Inputs Side: Composite Video Input • S-Video Input • Audio input for Composite

Outputs Rear: Video Output • Audio Outputs

Outputs Side: Headphone Jack

Rear



Side



Power: Internal power supply 3-prong grounded safety plug

Power Requirements: 120VAC (+/-)10%, 60Hz

Power Consumption: Stand-by: less than 1 watt (ENERGY STAR Qualified)

Cabinet: Construction: high-impact flame-retardant polystyrene
Finish: black
Dimensions: 18.5"H, 31.0"W, 4.0"D
Dimensions with stand: 20.7"H, 31.0"W, 9.1"D
VESA mounting compatible: 400 x 200 hole pattern

Weight: Product 46.3 lbs./Shipping 53.1 lbs.

Certification: UL Commercial Listing

Limited Warranty: 1 year parts and labor

This television receiver provides display of television closed-captioning in accordance with §15.119 of the FCC rules. This television does not support color attributes of television closed-captioning.

Optional Accessories

ClonePRO™ Remote (CBX203)

This unique accessory significantly reduces installation and programming time, allowing you to program one television and then transfer the same data to all similar sets in just seconds. The more RCA televisions you install, the more efficiency you gain.



Master Remote (R130K2)

The RCA Master Remote maintains control of all setup menus, including audio and video functions.



©2006 TTE Technology, Inc.
www.rca.com/rcacommercial • Phone: 1-800-333-7221

Commercial Sales and Distribution • MS INH605
101 West 103rd Street • Indianapolis, Indiana 46290-1024

Printed in U.S.A. 3/06-5M

TV pictures simulated. Specifications subject to change without notice. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. RCA and associated marks are trademarks of THOMSON S.A. used under license to TTE Corporation.



J26L637-0